

BLASTMAX GA Series Pump Unit



BLASTMAX™

The **BLASTMAX** GA series pump is our most popular and versatile pump. Available in several models for industrial cleaning, surface preparation or Hydrostatic Testing applications.



BLASTMAX GA 200 DT
Trailer Mounted

Pump Performance Range					
Pressure PSI [Bar]	Flow Rate GPM [LPM]				
Model No./HP	GA 75	GA 100	GA 150	GA 200	GA 250
40.000 [2758]	3.21 [12.15]	4.28 [16.20]	6.43 [24.34]	8.57 [32.44]	10.71 [40.54]
20.000 [1379]	6.43 [24.34]	8.57 [32.44]	12.86 [48.68]	17.14 [64.88]	21.43 [81.12]
15.000 [1034]	8.57 [32.44]	11.43 [43.27]	17.14 [64.88]	22.85 [86.50]	28.57 [108.15]
10,000 [689]	12.86 [48.68]	17.14 [64.88]	25.71 [97.32]	34.28 [129.76]	42.85 [162.20]
5,000 [343]	25.71 [97.32]	34.28 [129.76]	51.42 [194.64]	68.56 [259.52]	85.70 [324.41]

Flow rates are theoretical based on 100% volumetric and mechanical efficiency

Standard Features

Pump:

Horizontal, valve-in-line plungers

Water tank:

50 gallon water tank standard

Charge Pump:

Heavy duty cycle charge pump standard.

Suction plumbing:

Washable strainer and large capacity stainless steel bag type filter for up to 20,000 psi. 40,000 psi units equipped with 1 and 5 micron filters and charge pump.

Power transmission:

Kevlar reinforced synchronous drive system with safety belt guide.

Discharge plumbing:

Discharge manifold with interchangeable high pressure discharge connections, stainless steel glycerin filled pressure gauge and relief valve or rupture disc.



BLASTMAX GA 200 ES
Skid Mounted



Autopista Medellín Km. 2.7
Parque Industrial Los nogales Bod. 15
Cota (Cundinamarca)



Tes. (571+1)877-3686 Fax 8764539
Cel Ventas 317-6606052
Cel Presidencia: 317-4051319

www.ridecolombia.com Email: ridecomercial@ridecolombia.com rigerencia@ridecolombia.com